

RAD HIGH SPEED


Extreme duty torque wrenches with high RPM productivity

RAD High Speed torque wrenches incorporate a precision-engineered high-speed gearbox designed for faster run down and quick reaction point positioning on time sensitive bolting applications.

- The two-speed models feature a unique full automatic gearbox design, eliminating the time consuming switch between high and low speed gear.

FRL Unit:

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (FT.)		RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
			LOW	HIGH							
10644	10GX-2	0.75"	350	1000	85	9.9	80 db	10.3"	2.5"	2.75"	8.1"
17068	15DX-2	1.0"	500	1500	50	10.5	80 db	9.9"	2.7"	2.75"	8.1"
19773	25GX-2	1.0"	700	2500	44	16.6	80 db	12.0"	3.1"	3.3"	10.0"
24950	30DX-2	1.0"	1000	3000	49	16.1	80 db	12.2"	3.2"	2.75"	3.2"

Accuracy of +/-4%, Repeatability of +/-2%

RAD TORQUE SYSTEMS