


# B-RAD SELECT

**NEW! Now with digital torque settings.  
Torque ranges up to 4,000 Nm!**

The newly designed B-RAD Select offers unmatched power, versatility, and reliability while incorporating a new torque display with buttons. The B-RAD Select allows the user to easily select the target torque. Patented Product.

- Now with digital torque settings, able to increase or decrease the value by 10 Nm
- Torque ranges up to 4,000 NM
- Equipped with the latest lithium-ion technology
- Suitable for pre-torque and service jobs where electricity or compressed air are not available



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm)		RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
			LOW	HIGH						
24507	B-RAD SELECT 700	0.75"	175	700	13	3.4	235	63	67	260
24508	B-RAD SELECT 700-2	0.75"	200	700	58	4.1	285	63	67	260
24509	B-RAD SELECT 1400	0.75"	300	1,400	6	3.7	254	63	67	260
24510	B-RAD SELECT 1400-2	0.75"	300	1,400	20	4.5	301	63	67	260
24511	B-RAD SELECT 2000	1.0"	400	2,000	4	4.0	247	68	68	260
24512	B-RAD SELECT 2000-2	1.0"	400	2,000	18	4.8	330	68	68	260
25031	B-RAD SELECT 4000	1.0"	815	4,000	2	5.9	279	81	81	260
24929	B-RAD SELECT 4000-2	1.0"	815	4,000	13	7.3	411	81	81	260

Accuracy of +/-5%, Repeatability of +/-2%

**RAD TORQUE SYSTEMS**